

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Wilsonart 30/40 Adhesive
Product form : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Wilsonart LLC
P.O. Box 6110
Temple, TX 76503
Information phone: 800-433-3222 (USA)
In Case of Emergency Contact CHEMTREC (International): 703-527-3887

1.4. Emergency telephone number

Emergency number : CHEMTREC: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

STOT RE 2 H373

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : **Danger**

Hazard statements (GHS-US) : H360 - May damage fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P260 - Do not breathe vapours, mist
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear protective clothing, protective gloves
P302+P352 - If on skin: Wash with plenty of soap and water
P308+P313 - If exposed or concerned: Get medical advice/attention
P314 - Get medical advice/attention if you feel unwell
P321 - Specific treatment (see first aid instructions on this label)
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P405 - Store locked up
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Kaolin	(CAS No) 1332-58-7	1 - 5
Boric acid	(CAS No) 10043-35-3	0.5 - 1.5

Wilsonart 30/40/Wood Glue Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. Get medical attention immediately.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May cause an allergic skin reaction. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.
- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after skin contact : May cause an allergic skin reaction.
- Symptoms/injuries after eye contact : Direct contact with the eyes is likely to be irritating.
- Symptoms/injuries after ingestion : May cause gastrointestinal irritation.
- Chronic symptoms : May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry chemical. carbon dioxide (CO₂). Alcohol foam extinguishing media.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable.
- Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

6.1.1. For non-emergency personnel

- Protective equipment : Wear Protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Prevent entry to sewers and public waters.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

See Sections 8 and 13.

Wilsonart 30/40/Wood Glue Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Handle in accordance with good industrial hygiene and safety procedures. Use only in well-ventilated areas. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep the container tightly closed. Store in a dry, cool and well-ventilated place. Keep from freezing.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Boric acid (10043-35-3)	
ACGIH TWA (mg/m ³)	2 (inhalable fraction, listed under Borate compounds, inorganic)
ACGIH STEL (mg/m ³)	6 (inhalable fraction, listed under Borate compounds, inorganic)
Kaolin (1332-58-7)	
ACGIH TWA (mg/m ³)	2 (particulate matter containing no asbestos and < 1% crystalline silica, respirable fraction)
Remark (ACGIH)	Pneumoconiosis
OSHA PEL (TWA) (mg/m ³)	15 (total dust) 5 mg/m ³ (respirable fraction)

8.2. Exposure controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment : Gloves. Protective goggles. Insufficient ventilation: wear respiratory protection. Protective clothing.



Hand protection : Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection : Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection : Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection : Use NIOSH-approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Yellow. White.
Odor : Mild sweet.
Odor Threshold : No data available
pH : 4 - 5.5
Relative evaporation rate (butylacetate=1) : No data available
Melting point : Similar to water
Freezing point : Similar to water
Boiling point : Similar to water
Flash point : None.
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available

Wilsonart 30/40/Wood Glue Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Vapour pressure	: Equivalent to water
Relative vapour density at 20 °C	: Equivalent to water
Relative density	: 1.15 - 1.19
Solubility	: Soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : < 20 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Freezing and boiling temperatures.

10.5. Incompatible materials

Strong acids. Strong bases. Copper alloys. Copper. Oxidizing agent. Reducing agents.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂). Acetic acid. Various hydrocarbons. Sulfur oxides. Hydrogen Bromide. Hydrogen Chloride.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified pH: 4 - 5.5
Serious eye damage/irritation	: Not classified pH: 4 - 5.5
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Silica: Crystalline, quartz (14808-60-7)

IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: May damage fertility or the unborn child.
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/injuries after ingestion	: May cause gastrointestinal irritation.
Chronic symptoms	: May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Wilsonart 30/40/Wood Glue Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No information available.

12.2. Persistence and degradability

Wilsonart 30/31/40 Adhesive

Persistence and degradability	No information available.
-------------------------------	---------------------------

12.3. Bioaccumulative potential

Wilsonart 30/31/40 Adhesive

Bioaccumulative potential	No information available.
---------------------------	---------------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

In accordance with DOT

Not hazardous for transport

Additional information

Other information : No supplementary information available.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Wilsonart 30/31/40 Adhesive

All chemical substances in this product are listed on the Canadian Domestic Substances List (DSL) or are exempt

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

15.2. International regulations

No additional information available.

15.3. US State regulations

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

Methyl alcohol (67-56-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	Yes	No	No	

Silica: Crystalline, quartz (14808-60-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	

Wilsonart 30/40/Wood Glue Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Kaolin (1332-58-7)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Methyl alcohol (67-56-1)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Ethanolamine (141-43-5)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Phosphoric acid (7664-38-2)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Starch (9005-25-8)

U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) List


Silica: Crystalline, quartz (14808-60-7)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

SECTION 16: Other information

Indication of changes : Revision 1.0: New SDS Created.
Revision date : 12/01/2015
Other information : Author: MMJ.

NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard : 1 - Must be preheated before ignition can occur.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 3*
Flammability : 1
Physical : 0
Personal Protection :

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product