

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 09/29/2015

Supersedes: 01/30/2013

SDS# 19025

Version: 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Wilsonart 950/951; 980/981 Adhesive
Product form : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Adhesive for laminate

1.3. Details of the supplier of the safety data sheet

Wilsonart LLC
P.O. Box 6110
Temple, TX 76503-6110
Information phone: 800-433-3222 (USA)
In Case of Emergency Contact CHEMTREC (International): 703-527-3887

1.4. Emergency telephone number

Emergency number : CHEMTREC: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 2 H225
Skin Irrit. 2 H315
Eye Irrit. 2A H319
Skin Sens. 1 H317
Repr. 2 H361
STOT SE 3 H336
STOT RE 2 H373
Asp. Tox. 1 H304

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility. Suspected of damaging the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe spray, mist, vapours
P264 - Wash hands, forearms and face thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear eye protection, protective gloves, protective clothing
P301+P310 - IF SWALLOWED: Immediately call a doctor, a poison center
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention

Wilsonart 900 Series Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P314 - Get medical advice/attention if you feel unwell
P321 - Specific treatment (see first aid instructions on this label)
P331 - Do NOT induce vomiting
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P362+P364 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use dry extinguishing powder, carbon dioxide (CO₂), alcohol resistant foam to extinguish
P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % |
|---|---------------------|-----------|
| Acetone | (CAS No) 67-64-1 | 15 - 40 |
| Distillates, petroleum, light distillate hydrotreating process, low-boiling | (CAS No) 68410-97-9 | 10 - 30 |
| Cyclohexane | (CAS No) 110-82-7 | 7 - 13 |
| Isopentane | (CAS No) 78-78-4 | 7 - 13 |
| Pentane | (CAS No) 109-66-0 | 7 - 13 |
| Toluene | (CAS No) 108-88-3 | 7 - 13 |
| Naphtha, petroleum, hydrotreated light | (CAS No) 64742-49-0 | 0.5 - 1.5 |
| Hexane | (CAS No) 110-54-3 | 0.5 - 1.5 |
| Rosin | (CAS No) 8050-09-7 | 0.1 - 1 |

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.

First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.

First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.

First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes serious eye irritation. Suspected of damaging fertility. Suspected of damaging the unborn child. May cause an allergic skin reaction. Causes skin irritation. Causes damage to organs through prolonged or repeated exposure.

Symptoms/injuries after inhalation : May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : May cause an allergic skin reaction. Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child. . Causes damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

Wilsonart 900 Series Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide.

Unsuitable extinguishing media : Water.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.

Explosion hazard : Static discharge may serve as an ignition source for this product.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8). Avoid vapor formation. In case of spills, beware of slippery floors and surfaces. Eliminate all sources of ignition. Vapor may cause flash fires. Vapors are heavier than air and can travel long distances to ignition sources.

6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Remove all sources of ignition. Avoid breathing of vapors. Wear appropriate respirator and other protective clothing. Ventilate. Shut off source of leak only if safe to do so. Soak up with absorbent material, and place in non-leaking containers for proper disposal.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, sparks and open flames. Use adequate ventilation and avoid repeated or prolonged skin contact. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Ground/bond container and receiving equipment. Prohibit smoking in storage area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Isolate from oxidizers, heat, sparks, electrical equipment and open flame. Closed containers may explode if exposed to extreme heat. Store in a cool dry place. Prohibit smoking in storage area. Do not store with acids or oxidizers. Electrical service in storage area must be rated for flammable liquids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Rosin (8050-09-7) | |
|--|----------------------|
| Remark (ACGIH) | OELs not established |
| Remark (OSHA) | OELs not established |
| Distillates, petroleum, light distillate hydrotreating process, low-boiling (68410-97-9) | |
| Remark (ACGIH) | OELs not established |
| Remark (OSHA) | OELs not established |

Wilsonart 900 Series Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|--|---|
| Cyclohexane (110-82-7) | |
| ACGIH TWA (ppm) | 100 ppm |
| OSHA PEL (TWA) (mg/m ³) | 1050 mg/m ³ |
| OSHA PEL (TWA) (ppm) | 300 ppm |
| Isopentane (78-78-4) | |
| ACGIH TWA (ppm) | 600 ppm (listed under Pentane, all isomers) |
| Remark (OSHA) | OELs not established |
| Pentane (109-66-0) | |
| ACGIH TWA (ppm) | 600 ppm (listed under Pentane, all isomers) |
| OSHA PEL (TWA) (mg/m ³) | 2950 mg/m ³ |
| OSHA PEL (TWA) (ppm) | 1000 ppm |
| Naphtha, petroleum, hydrotreated light (64742-49-0) | |
| Remark (ACGIH) | OELs not established |
| Remark (OSHA) | OELs not established |
| Hexane (110-54-3) | |
| ACGIH TWA (ppm) | 50 ppm |
| OSHA PEL (TWA) (mg/m ³) | 1800 mg/m ³ |
| OSHA PEL (TWA) (ppm) | 500 ppm |
| Toluene (108-88-3) | |
| ACGIH TWA (ppm) | 20 ppm |
| Remark (ACGIH) | Visual impair; female repro; |
| Acetone (67-64-1) | |
| ACGIH TWA (ppm) | 500 ppm |
| ACGIH STEL (ppm) | 750 ppm |
| OSHA PEL (TWA) (mg/m ³) | 2400 mg/m ³ |
| OSHA PEL (TWA) (ppm) | 1000 ppm |
| OSHA PEL (STEL) (mg/m ³) | 2400 mg/m ³ (The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors) |
| OSHA PEL (STEL) (ppm) | 1000 ppm |

8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

: Safety glasses. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Hand protection

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.

Eye protection

: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection

: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection

: Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Wilsonart 900 Series Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|--|
| Physical state | : Liquid |
| Color | : Red (950.) Brown/Yellow (951.) |
| Odor | : strong. Solvent. |
| Odor Threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point | : 6.5 °C May begin to solidify for cyclohexane (43.7 °F) |
| Freezing point | : No data available |
| Boiling point | : 56 °C (132 °F) for acetone |
| Flash point | : -9.6 °C Closed Cup (14.7 °F) |
| Auto-ignition temperature | : 225 °C for lowest known component - Light Hydrotreated Distillate (437 °F) |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapour pressure | : 268 mm Hg at 20 °C (calculated) |
| Relative vapour density at 20 °C | : 2.65 Weighted Average (Air = 1); Highest component is 3.14 for Toluene |
| Relative density | : No data available |
| Density | : 6.6 lb/gal |
| Solubility | : Water: Not soluble in water |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : 150 – 200 cP |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |
| Explosive limits | : 2 - 13 vol % LEL for lowest known component - Toluene; UEL for highest known component - Acetone |

9.2. Other information

| | |
|------------------|----------------------------|
| VOC content | : 606 g/l |
| Other properties | : Percent Volatile: 82.5%. |

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Heat, flame. Ignition sources.

10.5. Incompatible materials

Strong acids and alkalis, oxidizing agents, reducing agents, copper and copper alloys.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂). Various hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| Rosin (8050-09-7) | |
|----------------------------|--------------|
| LD50 oral rat | 7600 mg/kg |
| LD50 dermal rabbit | > 2500 mg/kg |
| LC50 inhalation rat (mg/l) | 1.5 mg/l/4h |

Wilsonart 900 Series Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Cyclohexane (110-82-7) | |
|-------------------------------|--------------|
| LD50 oral rat | 12705 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat (mg/l) | 13.9 mg/l/4h |

| Isopentane (78-78-4) | |
|-----------------------------|------------------------------|
| LC50 inhalation rat (mg/l) | 280000 mg/m ³ 4 h |

| Pentane (109-66-0) | |
|----------------------------|--------------------------|
| LD50 oral rat | > 2000 mg/kg |
| LD50 dermal rabbit | 3000 mg/kg |
| LC50 inhalation rat (mg/l) | 364 g/m ³ 4 h |

| Naphtha, petroleum, hydrotreated light (64742-49-0) | |
|--|--------------|
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 3160 mg/kg |
| LC50 inhalation rat (ppm) | 73680 ppm/4h |

| Hexane (110-54-3) | |
|---------------------------|--------------|
| LD50 dermal rabbit | 3000 mg/kg |
| LC50 inhalation rat (ppm) | 48000 ppm/4h |

| Toluene (108-88-3) | |
|----------------------------|--------------|
| LD50 oral rat | 2600 mg/kg |
| LD50 dermal rabbit | 12000 mg/kg |
| LC50 inhalation rat (mg/l) | 12.5 mg/l/4h |

| Acetone (67-64-1) | |
|----------------------------|-------------------------|
| LC50 inhalation rat (mg/l) | 50100 mg/m ³ |

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified.
Carcinogenicity : Not classified.

| Toluene (108-88-3) | |
|---------------------------|----------------------|
| IARC group | 3 - Not classifiable |

Reproductive toxicity : Suspected of damaging fertility. Suspected of damaging the unborn child.
Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard : May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation : May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact : May cause an allergic skin reaction. Causes skin irritation.
Symptoms/injuries after eye contact : Causes serious eye irritation.
Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.
Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child. . Causes damage to organs through prolonged or repeated exposure.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No data available.

| Hexane (110-54-3) | |
|--------------------------|---|
| LC50 fishes 1 | 2.1 - 2.98 mg/l 96 Hr LC50 Pimephales promelas [flow-through] |

12.2. Persistence and degradability

| Wilsonart 950/951 Adhesive | |
|-----------------------------------|-----------------------------------|
| Persistence and degradability | The product is not biodegradable. |

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

Wilsonart 900 Series Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.
- Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

In accordance with DOT

- Transport document description : UN1133 Adhesives, containing a flammable liquid, 3, II
- UN-No.(DOT) : 1133
- DOT NA no. : UN1133
- Proper Shipping Name (DOT) : Adhesives, containing a flammable liquid
- Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : II - Medium Danger
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
- DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Additional information

- Other information : **Limited Quantity Exception**-flammable liquids in Packing Group II, inner packagings not over 5.0 L (1.3 gallons) net capacity each, 172.102 exception 149, packed in a strong outer packaging.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Wilsonart 950/951 Adhesive

All components of this product are listed on the TSCA Inventory or are exempt

| | |
|-------------------------------------|---|
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard |
|-------------------------------------|---|

| | |
|-----------------------|----------------------------------|
| | CAS #: 108-88-3 (Toluene) |
| Section 302 (EHS) TPQ | lb |
| Section 304 EHS RQ | lb |
| CERCLA RQ | 1000 lb |
| Section 313 | Listed on US SARA Section 313 |

| | |
|--|--------------------------------------|
| | CAS #: 110-82-7 (Cyclohexane) |
|--|--------------------------------------|

Wilsonart 900 Series Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|-----------------------|-------------------------------|
| Section 302 (EHS) TPQ | lb |
| Section 304 EHS RQ | lb |
| CERCLA RQ | 1000 lb |
| Section 313 | Listed on US SARA Section 313 |

| | | |
|-----------------------|---------------|-------------------------------|
| | CAS #: | 110-54-3 (n-hexane) |
| Section 302 (EHS) TPQ | | lb |
| Section 304 EHS RQ | | lb |
| CERCLA RQ | | 5000 lb |
| Section 313 | | Listed on US SARA Section 313 |

| | | |
|-----------------------|---------------|--------------------------|
| | CAS #: | 67-64-1 (Acetone) |
| Section 302 (EHS) TPQ | | lb |
| Section 304 EHS RQ | | lb |
| CERCLA RQ | | 5000 lb |
| Section 313 | | Not Listed |

15.2. International regulations

CANADA

No additional information available.

15.3. US State regulations

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

| Ethylbenzene (100-41-4) | | | | |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes | No | No | No | 54 µg/day |

| Formaldehyde (50-00-0) | | | | |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes | No | No | No | |

| Benzene (71-43-2) | | | | |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes | Yes | No | Yes | 6.4 µg/day |

| Toluene (108-88-3) | | | | |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| No | Yes | No | No | 7000 µg/day |

| Talc (14807-96-6) | | | | |
|--|--|--|--|--|
| U.S. - Massachusetts - Right To Know List | | | | |
| U.S. - New Jersey - Right to Know Hazardous Substance List | | | | |
| U.S. - Pennsylvania - RTK (Right to Know) List | | | | |

| Magnesium oxide (1309-48-4) | | | | |
|--|--|--|--|--|
| U.S. - New Jersey - Right to Know Hazardous Substance List | | | | |
| U.S. - Pennsylvania - RTK (Right to Know) List | | | | |
| U.S. - Massachusetts - Right To Know List | | | | |

Wilsonart 900 Series Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Cyclohexane (110-82-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Isopentane (78-78-4)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Pentane (109-66-0)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Hexane (110-54-3)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Benzene (71-43-2)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Toluene (108-88-3)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List


Acetone (67-64-1)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : New SDS Created.
Revision date : 09/29/2015
Other information : Author: ZPT.

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 2
Flammability : 4
Physical : 0
Personal Protection :

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product